




Keeping You Connected.



SEMI
PREMIUMCONNECTIONS
FIELD TESTED. FIELD PROVEN.

Precision Connections BK

4.5 in. 11.6 lb/ft P-110 with 5 in. Coupling OD

Pipe Body

Nominal OD	4.500	inches
Nominal Weight	11.60	lb/ft
Wall Thickness	0.25	inches
Plain End Weight	11.35	lb/ft
Drift	3.875	inches
Nominal ID	4.000	inches
Grade	P-110	
Min Yield	110,000	lbf/in ²
Min Tensile	125,000	lbf/in ²
Critical Section Area	3.338	in ²
Pipe Body Yield Strength	367	kips
Min Internal Yield Pressure	10,690	psi
Collapse Pressure	7,580	psi


Connection

Coupling OD	5.000	inches
Coupling Length	7.875	inches
Make Up Loss	3.938	inches
Critical Section Area	4.472	in ²
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	100%	
Connection Strength	367	kips
Compression Efficiency	100%	
Uniaxial Bend Rating	100.9	° / 100 ft
Min Make Up Torque	2,150	ft-lbs
Yield Torque	8,200	ft-lbs

v1.2

7/26/2018

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.



Torque Data Sheet - Precision Connections BK

4.5 in. 11.6 lb/ft P-110 with 5 in. Coupling OD

Min Make Up Torque	2,150	ft-lbs	Max Operating Torque	6,950	ft-lbs
Max Make Up Torque	6,150	ft-lbs	Yield Torque	8,200	ft-lbs
Optimum Torque	2,950	ft-lbs			

Representative Torque Turn Graph

