




Keeping You Connected.

Precision Connections BK

4.5 in. 13.5 lb/ft CYP-110 with 5 in. Coupling OD



SEMI
PREMIUMCONNECTIONS
FIELD TESTED. FIELD PROVEN.

Pipe Body

Nominal OD	4.500	inches
Nominal Weight	13.50	lb/ft
Wall Thickness	0.29	inches
Plain End Weight	13.04	lb/ft
Drift	3.795	inches
Nominal ID	3.920	inches
Grade	CYP-110	
Min Yield	110,000	lbf/in ²
Min Tensile	125,000	lbf/in ²
Critical Section Area	3.836	in ²
Pipe Body Yield Strength	422	kips
Min Internal Yield Pressure	12,410	psi
Collapse Pressure	10,690	psi

Connection


Coupling OD	5.000	inches
Coupling Length	7.875	inches
Make Up Loss	3.938	inches
Critical Section Area	4.472	in ²
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	100%	
Connection Strength	422	kips
Compression Efficiency	100%	
Uniaxial Bend Rating	100.9	° / 100 ft
Min Make Up Torque	2,800	ft-lbs
Yield Torque	10,750	ft-lbs



v1.2

7/26/2018

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.



Torque Data Sheet - Precision Connections BK

4.5 in. 13.5 lb/ft CYP-110 with 5 in. Coupling OD

Min Make Up Torque 2,800 ft-lbs


Max Make Up Torque 8,050 ft-lbs

Optimum Torque 3,850 ft-lbs

Max Operating Torque 9,150 ft-lbs

Yield Torque 10,750 ft-lbs

Representative Torque Turn Graph



v1.2

7/26/2018