




Keeping You Connected.

Precision Connections BK

9.625 in. 43.5 lb/ft HC-P110 with 10.625 in. Coupling OD



SEMI
PREMIUMCONNECTIONS
FIELD TESTED. FIELD PROVEN.

Pipe Body

Nominal OD	9.625	inches
Nominal Weight	43.50	lb/ft
Wall Thickness	0.435	inches
Plain End Weight	42.69	lb/ft
Drift	8.599	inches
Nominal ID	8.755	inches
Grade	HC-P110	
Min Yield	110,000	lbf/in ²
Min Tensile	125,000	lbf/in ²
Critical Section Area	12.559	in ²
Pipe Body Yield Strength	1381	kips
Min Internal Yield Pressure	8,700	psi
Collapse Pressure	5,440	psi

Connection

Coupling OD	10.625	inches
Coupling Length	9.625	inches
Make Up Loss	4.813	inches
Critical Section Area	18.558	in ²
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	100%	
Connection Strength	1381	kips
Compression Efficiency	100%	
Uniaxial Bend Rating	47.4	° / 100 ft
Min Make Up Torque	10,000	ft-lbs
Yield Torque	86,950	ft-lbs

v1.2

7/26/2018

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.



Torque Data Sheet - Precision Connections BK

9.625 in. 43.5 lb/ft HC-P110 with 10.625 in. Coupling OD

Min Make Up Torque 10,000 ft-lbs


Max Make Up Torque 65,200 ft-lbs

Optimum Torque 20,000 ft-lbs

Max Operating Torque 73,900 ft-lbs

Yield Torque 86,950 ft-lbs

Representative Torque Turn Graph



v1.2

7/26/2018