




Keeping You Connected.

Precision Connections BK

9.625 in. 47 lb/ft P-110 with 10.625 in. Coupling OD



SEMI
PREMIUMCONNECTIONS
FIELD TESTED. FIELD PROVEN.

Pipe Body

Nominal OD	9.625	inches
Nominal Weight	47.00	lb/ft
Wall Thickness	0.472	inches
Plain End Weight	46.14	lb/ft
Drift	8.525	inches
Nominal ID	8.681	inches
Grade	P-110	
Min Yield	110,000	lbf/in ²
Min Tensile	125,000	lbf/in ²
Critical Section Area	13.572	in ²
Pipe Body Yield Strength	1493	kips
Min Internal Yield Pressure	9,440	psi
Collapse Pressure	5,300	psi


Connection

Coupling OD	10.625	inches
Coupling Length	9.625	inches
Make Up Loss	4.813	inches
Critical Section Area	18.558	in ²
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	100%	
Connection Strength	1493	kips
Compression Efficiency	100%	
Uniaxial Bend Rating	47.4	° / 100 ft
Min Make Up Torque	10,000	ft-lbs
Yield Torque	98,100	ft-lbs

v1.2

7/26/2018

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.



Torque Data Sheet - Precision Connections BK

9.625 in. 47 lb/ft P-110 with 10.625 in. Coupling OD

Min Make Up Torque 10,000 ft-lbs


Max Make Up Torque 73,600 ft-lbs

Optimum Torque 20,000 ft-lbs

Max Operating Torque 83,400 ft-lbs

Yield Torque 98,100 ft-lbs

Representative Torque Turn Graph



v1.2

7/26/2018