




Keeping You Connected.



SEMI
PREMIUMCONNECTIONS
FIELD TESTED. FIELD PROVEN.

Precision Connections BK-HT

5 in. 21.4 lb/ft Q-125 with 5.75 in. Coupling OD

Pipe Body

Nominal OD	5.000	inches
Nominal Weight	21.40	lb/ft
Wall Thickness	0.437	inches
Plain End Weight	21.30	lb/ft
Drift	4.001	inches
Nominal ID	4.126	inches
Grade	Q-125	
Min Yield	125,000	lbf/in ²
Min Tensile	135,000	lbf/in ²
Critical Section Area	6.264	in ²
Pipe Body Yield Strength	783	kips
Min Internal Yield Pressure	19,120	psi
Collapse Pressure	19,940	psi

Connection

Coupling OD	5.750	inches
Coupling Length	8.125	inches
Make Up Loss	4.063	inches
Critical Section Area	7.240	in ²
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	100%	
Connection Strength	783	kips
Compression Efficiency	100%	
Uniaxial Bend Rating	99.7	° / 100 ft
Min Make Up Torque	7,500	ft-lbs
Yield Torque	28,900	ft-lbs

v1.2

7/26/2018

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.




Torque Data Sheet - Precision Connections BK-HT

5 in. 21.4 lb/ft Q-125 with 5.75 in. Coupling OD

Min Make Up Torque	7,500	ft-lbs
Max Make Up Torque	21,700	ft-lbs
Optimum Torque	10,400	ft-lbs

Max Operating Torque	24,600	ft-lbs
Yield Torque	28,900	ft-lbs

Representative Torque Turn Graph



v1.2

7/26/2018