




Keeping You Connected.



SEMI
PREMIUMCONNECTIONS
FIELD TESTED. FIELD PROVEN.

Precision Connections BK-HT

7.625 in. 39 lb/ft HC-P110 with 8.5 in. Coupling OD

Pipe Body

Nominal OD	7.625	inches
Nominal Weight	39.00	lb/ft
Wall Thickness	0.5	inches
Plain End Weight	38.05	lb/ft
Drift	6.500	inches
Nominal ID	6.625	inches
Grade	HC-P110	
Min Yield	110,000	lbf/in ²
Min Tensile	125,000	lbf/in ²
Critical Section Area	11.192	in ²
Pipe Body Yield Strength	1231	kips
Min Internal Yield Pressure	12,620	psi
Collapse Pressure	12,180	psi


Connection

Coupling OD	8.500	inches
Coupling Length	9.375	inches
Make Up Loss	4.688	inches
Critical Section Area	13.063	in ²
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	100%	
Connection Strength	1231	kips
Compression Efficiency	100%	
Uniaxial Bend Rating	59.3	° / 100 ft
Min Make Up Torque	10,000	ft-lbs
Yield Torque	66,500	ft-lbs

v1.2

7/26/2018

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.




Torque Data Sheet - Precision Connections BK-HT

7.625 in. 39 lb/ft HC-P110 with 8.5 in. Coupling OD

Min Make Up Torque	10,000	ft-lbs
Max Make Up Torque	49,900	ft-lbs
Optimum Torque	20,000	ft-lbs

Max Operating Torque	56,550	ft-lbs
Yield Torque	66,500	ft-lbs

Representative Torque Turn Graph



v1.2

7/26/2018