




Keeping You Connected.



SEMI  
**PREMIUMCONNECTIONS**  
FIELD TESTED. FIELD PROVEN.

## Precision Connections BK-HT

6.625 in. 32 lb/ft HC-L80 with 7.475 in. Coupling OD

### Pipe Body

Nominal OD	6.625	inches
Nominal Weight	32.00	lb/ft
Wall Thickness	0.475	inches
Plain End Weight	31.20	lb/ft
Drift	5.550	inches
Nominal ID	5.675	inches
Grade	HC-L80	
Min Yield	80,000	lbf/in <sup>2</sup>
Min Tensile	95,000	lbf/in <sup>2</sup>
Critical Section Area	9.177	in <sup>2</sup>
Pipe Body Yield Strength	734	kips
Min Internal Yield Pressure	10,040	psi
Collapse Pressure	#VALUE! psi	

### Connection


Coupling OD	7.475	inches
Coupling Length	8.625	inches
Make Up Loss	4.313	inches
Critical Section Area	10.852	in <sup>2</sup>
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	100%	
Connection Strength	734	kips
Compression Efficiency	100%	
Uniaxial Bend Rating	49.0	° / 100 ft
Min Make Up Torque	8,500	ft-lbs
Yield Torque	32,750	ft-lbs



v1.2

1/3/2019

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.



## Torque Data Sheet - Precision Connections BK-HT

6.625 in. 32 lb/ft HC-L80 with 7.475 in. Coupling OD

Min Make Up Torque	8,500	ft-lbs	Max Operating Torque	27,800	ft-lbs
Max Make Up Torque	24,550	ft-lbs	Yield Torque	32,750	ft-lbs
Optimum Torque	11,800	ft-lbs			

**Representative Torque Turn Graph**

