




Keeping You Connected.

Precision Connections BK

5.5 in. 23 lb/ft P-110 with 6.05 in. Coupling OD



SEMI
PREMIUMCONNECTIONS
FIELD TESTED. FIELD PROVEN.

Pipe Body

Nominal OD	5.500	inches
Nominal Weight	23.00	lb/ft
Wall Thickness	0.415	inches
Plain End Weight	22.54	lb/ft
Drift	4.545	inches
Nominal ID	4.670	inches
Grade	P-110	
Min Yield	110,000	lbf/in ²
Min Tensile	125,000	lbf/in ²
Critical Section Area	6.630	in ²
Pipe Body Yield Strength	729	kips
Min Internal Yield Pressure	14,530	psi
Collapse Pressure	14,540	psi


Connection

Coupling OD	6.050	inches
Coupling Length	8.250	inches
Make Up Loss	4.125	inches
Critical Section Area	6.031	in ²
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	91%	
Connection Strength	664	kips
Compression Efficiency	100%	
Uniaxial Bend Rating	83.4	° / 100 ft
Min Make Up Torque	7,250	ft-lbs
Yield Torque	27,800	ft-lbs

v1.2

7/26/2018

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.



Torque Data Sheet - Precision Connections BK

5.5 in. 23 lb/ft P-110 with 6.05 in. Coupling OD

Min Make Up Torque 7,250 ft-lbs


Max Make Up Torque 20,850 ft-lbs

Optimum Torque 10,000 ft-lbs

Max Operating Torque 23,650 ft-lbs

Yield Torque 27,800 ft-lbs

Representative Torque Turn Graph



v1.2

7/26/2018