



Keeping You Connected.



SEMI PREMIUM CONNECTIONS  
FIELD TESTED. FIELD PROVEN.

## Precision Connections BK

### 9.625 in. 40 lb/ft P110 EC with 10.625 in. Coupling OD

#### Pipe Body

Nominal OD	9.625	inches
Nominal Weight	40.00	lb/ft
Wall Thickness	0.395	inches
Plain End Weight	38.94	lb/ft
Drift	8.750	inches
Nominal ID	8.835	inches
Grade	P110 EC	
Min Yield	125,000	lbf/in <sup>2</sup>
Min Tensile	135,000	lbf/in <sup>2</sup>
Critical Section Area	11.454	in <sup>2</sup>
Pipe Body Yield Strength	1432	kips
Min Internal Yield Pressure	8,980	psi
Collapse Pressure	3,530	psi


#### Connection

Coupling OD	10.625	inches
Coupling Length	9.625	inches
Make Up Loss	4.813	inches
Critical Section Area	18.558	in <sup>2</sup>
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	100%	
Connection Strength	1432	kips
Compression Efficiency	100%	
Uniaxial Bend Rating	53.9	° / 100 ft
Min Make Up Torque	10,000	ft-lbs
Yield Torque	85,050	ft-lbs

v1.2

7/26/2018

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.



**Torque Data Sheet - Precision Connections BK**

**9.625 in. 40 lb/ft P110 EC with 10.625 in. Coupling OD**

Min Make Up Torque	10,000	ft-lbs	Max Operating Torque	72,300	ft-lbs
Max Make Up Torque	63,800	ft-lbs	Yield Torque	85,050	ft-lbs
Optimum Torque	20,000	ft-lbs			

**Representative Torque Turn Graph**

