



Keeping You Connected.



SEMI
PREMIUMCONNECTIONS
FIELD TESTED. FIELD PROVEN.

Precision Connections BK-HT

5 in. 23.2 lb/ft L-80 with 5.75 in. Coupling OD

Pipe Body

Nominal OD	5.000	inches
Nominal Weight	23.20	lb/ft
Wall Thickness	0.478	inches
Plain End Weight	23.09	lb/ft
Drift	3.919	inches
Nominal ID	4.044	inches
Grade	L-80	
Min Yield	80,000	lbf/in ²
Min Tensile	95,000	lbf/in ²
Critical Section Area	6.791	in ²
Pipe Body Yield Strength	543	kips
Min Internal Yield Pressure	13,380	psi
Collapse Pressure	13,830	psi

Connection

Coupling OD	5.750	inches
Coupling Length	8.125	inches
Make Up Loss	4.063	inches
Critical Section Area	7.240	in ²
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	100%	
Connection Strength	543	kips
Compression Efficiency	100%	
Uniaxial Bend Rating	63.8	° / 100 ft
Min Make Up Torque	5,350	ft-lbs
Yield Torque	20,550	ft-lbs

v1.2

7/26/2018

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.



Torque Data Sheet - Precision Connections BK-HT

5 in. 23.2 lb/ft L-80 with 5.75 in. Coupling OD

Min Make Up Torque 5,350 ft-lbs


Max Make Up Torque 15,400 ft-lbs

Optimum Torque 7,400 ft-lbs

Max Operating Torque 17,450 ft-lbs

Yield Torque 20,550 ft-lbs

Representative Torque Turn Graph



v1.2

7/26/2018