



Keeping You Connected.



SEMI
PREMIUMCONNECTIONS
FIELD TESTED. FIELD PROVEN.

Precision Connections BK-HT

5 in. 23.2 lb/ft Q-125 with 5.75 in. Coupling OD

Pipe Body

Nominal OD	5.000	inches
Nominal Weight	23.20	lb/ft
Wall Thickness	0.478	inches
Plain End Weight	23.09	lb/ft
Drift	3.919	inches
Nominal ID	4.044	inches
Grade	Q-125	
Min Yield	125,000	lbf/in ²
Min Tensile	135,000	lbf/in ²
Critical Section Area	6.791	in ²
Pipe Body Yield Strength	849	kips
Min Internal Yield Pressure	20,910	psi
Collapse Pressure	21,620	psi


Connection

Coupling OD	5.750	inches
Coupling Length	8.125	inches
Make Up Loss	4.063	inches
Critical Section Area	7.240	in ²
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	100%	
Connection Strength	849	kips
Compression Efficiency	100%	
Uniaxial Bend Rating	99.7	° / 100 ft
Min Make Up Torque	8,350	ft-lbs
Yield Torque	32,100	ft-lbs

v1.2

7/26/2018

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.



Torque Data Sheet - Precision Connections BK-HT

5 in. 23.2 lb/ft Q-125 with 5.75 in. Coupling OD

Min Make Up Torque 8,350 ft-lbs


Max Make Up Torque 24,100 ft-lbs

Optimum Torque 11,550 ft-lbs

Max Operating Torque 27,300 ft-lbs

Yield Torque 32,100 ft-lbs

Representative Torque Turn Graph



v1.2

7/26/2018