



Keeping You Connected.



SEMI
PREMIUMCONNECTIONS
FIELD TESTED. FIELD PROVEN.

Precision Connections BK-HT

5.5 in. 26 lb/ft Q-125 with 6.3 in. Coupling OD

Pipe Body

Nominal OD	5.500	inches
Nominal Weight	26.00	lb/ft
Wall Thickness	0.476	inches
Plain End Weight	25.55	lb/ft
Drift	4.545	inches
Nominal ID	4.548	inches
Grade	Q-125	
Min Yield	125,000	lbf/in ²
Min Tensile	135,000	lbf/in ²
Critical Section Area	7.513	in ²
Pipe Body Yield Strength	939	kips
Min Internal Yield Pressure	18,930	psi
Collapse Pressure	19,760	psi


Connection

Coupling OD	6.300	inches
Coupling Length	8.250	inches
Make Up Loss	4.125	inches
Critical Section Area	8.456	in ²
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	100%	
Connection Strength	939	kips
Compression Efficiency	100%	
Uniaxial Bend Rating	91.0	° / 100 ft
Min Make Up Torque	10,000	ft-lbs
Yield Torque	47,750	ft-lbs

v1.2

7/26/2018

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.



Torque Data Sheet - Precision Connections BK-HT

5.5 in. 26 lb/ft Q-125 with 6.3 in. Coupling OD

Min Make Up Torque 10,000 ft-lbs


Max Make Up Torque 35,800 ft-lbs

Optimum Torque 17,200 ft-lbs

Max Operating Torque 40,550 ft-lbs

Yield Torque 47,750 ft-lbs

Representative Torque Turn Graph



v1.2

7/26/2018