



Keeping You Connected.



SEMI PREMIUM CONNECTIONS
FIELD TESTED. FIELD PROVEN.

Precision Connections BK-HT

7 in. 29 lb/ft Q-125 with 7.875 in. Coupling OD

Pipe Body

Nominal OD	7.000	inches
Nominal Weight	29.00	lb/ft
Wall Thickness	0.408	inches
Plain End Weight	28.72	lb/ft
Drift	6.125	inches
Nominal ID	6.184	inches
Grade	Q-125	
Min Yield	125,000	lbf/in ²
Min Tensile	135,000	lbf/in ²
Critical Section Area	8.449	in ²
Pipe Body Yield Strength	1056	kips
Min Internal Yield Pressure	12,750	psi
Collapse Pressure	9,110	psi


Connection

Coupling OD	7.875	inches
Coupling Length	9.000	inches
Make Up Loss	4.500	inches
Critical Section Area	11.859	in ²
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	100%	
Connection Strength	1056	kips
Compression Efficiency	100%	
Uniaxial Bend Rating	72.8	° / 100 ft
Min Make Up Torque	10,000	ft-lbs
Yield Torque	48,300	ft-lbs

v1.2

7/26/2018

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.



Torque Data Sheet - Precision Connections BK-HT

7 in. 29 lb/ft Q-125 with 7.875 in. Coupling OD

Min Make Up Torque	10,000	ft-lbs	Max Operating Torque	41,050	ft-lbs
Max Make Up Torque	36,200	ft-lbs	Yield Torque	48,300	ft-lbs
Optimum Torque	17,400	ft-lbs			

Representative Torque Turn Graph

