




Keeping You Connected.



SEMI PREMIUM CONNECTIONS FIELD TESTED. FIELD PROVEN.

Precision Connections BK

6.625 in. 24 lb/ft P-110 with 7.39 in. Coupling OD

Pipe Body

Nominal OD	6.625	inches
Nominal Weight	24.00	lb/ft
Wall Thickness	0.352	inches
Plain End Weight	23.58	lb/ft
Drift	5.796	inches
Nominal ID	5.921	inches
Grade	P-110	
Min Yield	110,000	lbf/in ²
Min Tensile	125,000	lbf/in ²
Critical Section Area	6.937	in ²
Pipe Body Yield Strength	763	kips
Min Internal Yield Pressure	10,230	psi
Collapse Pressure	6,730	psi

Connection

Coupling OD	7.390	inches
Coupling Length	8.625	inches
Make Up Loss	4.313	inches
Critical Section Area	9.860	in ²
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	100%	
Connection Strength	763	kips
Compression Efficiency	100%	
Uniaxial Bend Rating	68.2	° / 100 ft
Min Make Up Torque	5,550	ft-lbs
Yield Torque	21,250	ft-lbs

v1.2

1/3/2019

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.



Torque Data Sheet - Precision Connections BK

6.625 in. 24 lb/ft P-110 with 7.39 in. Coupling OD

Min Make Up Torque	5,550	ft-lbs	Max Operating Torque	18,050	ft-lbs
Max Make Up Torque	15,950	ft-lbs	Yield Torque	21,250	ft-lbs
Optimum Torque	7,650	ft-lbs			

Representative Torque Turn Graph

