




Keeping You Connected.



SEMI  
**PREMIUMCONNECTIONS**  
FIELD TESTED. FIELD PROVEN.

## Precision Connections BK-HT

6.625 in. 28 lb/ft L-80 with 7.475 in. Coupling OD

### Pipe Body

Nominal OD	6.625	inches
Nominal Weight	28.00	lb/ft
Wall Thickness	0.417	inches
Plain End Weight	27.65	lb/ft
Drift	5.666	inches
Nominal ID	5.791	inches
Grade	L-80	
Min Yield	80,000	lbf/in <sup>2</sup>
Min Tensile	95,000	lbf/in <sup>2</sup>
Critical Section Area	8.133	in <sup>2</sup>
Pipe Body Yield Strength	651	kips
Min Internal Yield Pressure	8,810	psi
Collapse Pressure	8,170	psi

### Connection

Coupling OD	7.475	inches
Coupling Length	8.625	inches
Make Up Loss	4.313	inches
Critical Section Area	10.852	in <sup>2</sup>
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	100%	
Connection Strength	651	kips
Compression Efficiency	100%	
Uniaxial Bend Rating	49.0	° / 100 ft
Min Make Up Torque	7,200	ft-lbs
Yield Torque	27,650	ft-lbs

v1.2

1/3/2019

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.




## Torque Data Sheet - Precision Connections BK-HT

6.625 in. 28 lb/ft L-80 with 7.475 in. Coupling OD

Min Make Up Torque	7,200	ft-lbs
Max Make Up Torque	20,750	ft-lbs
Optimum Torque	9,950	ft-lbs

Max Operating Torque	23,500	ft-lbs
Yield Torque	27,650	ft-lbs

**Representative Torque Turn Graph**



v1.2

1/3/2019