



Keeping You Connected.



SEMI
PREMIUMCONNECTIONS
FIELD TESTED. FIELD PROVEN.

Precision Connections BK-HT

6.625 in. 28 lb/ft Q-125 with 7.475 in. Coupling OD

Pipe Body

Nominal OD	6.625	inches
Nominal Weight	28.00	lb/ft
Wall Thickness	0.417	inches
Plain End Weight	27.65	lb/ft
Drift	5.666	inches
Nominal ID	5.791	inches
Grade	Q-125	
Min Yield	125,000	lbf/in ²
Min Tensile	135,000	lbf/in ²
Critical Section Area	8.133	in ²
Pipe Body Yield Strength	1017	kips
Min Internal Yield Pressure	13,770	psi
Collapse Pressure	10,990	psi

Connection

Coupling OD	7.475	inches
Coupling Length	8.625	inches
Make Up Loss	4.313	inches
Critical Section Area	10.852	in ²
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	100%	
Connection Strength	1017	kips
Compression Efficiency	100%	
Uniaxial Bend Rating	76.7	° / 100 ft
Min Make Up Torque	10,000	ft-lbs
Yield Torque	43,200	ft-lbs

v1.2

1/3/2019

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.




Torque Data Sheet - Precision Connections BK-HT

6.625 in. 28 lb/ft Q-125 with 7.475 in. Coupling OD

Min Make Up Torque	10,000	ft-lbs
Max Make Up Torque	32,400	ft-lbs
Optimum Torque	15,550	ft-lbs

Max Operating Torque	36,700	ft-lbs
Yield Torque	43,200	ft-lbs

Representative Torque Turn Graph



v1.2

1/3/2019