



SEMI
PREMIUMCONNECTIONS
FIELD TESTED. FIELD PROVEN.

Precision Connections BK-FX

7 in. 29 lb/ft P-110 with 7.875 in. Coupling OD

Pipe Body

Nominal OD	7.000	inches
Nominal Weight	29.00	lb/ft
Wall Thickness	0.408	inches
Plain End Weight	28.72	lb/ft
Drift	6.125	inches
Nominal ID	6.184	inches
<hr/>		
Grade	P-110	
Min Yield	110,000	lbf/in ²
Min Tensile	125,000	lbf/in ²
Critical Section Area	8.449	in ²
Pipe Body Yield Strength	929	kips
Min Internal Yield Pressure	11,220	psi
Collapse Pressure	8,530	psi

Connection

Coupling OD	7.875	inches
Coupling Length	9.625	inches
Make Up Loss	4.500	inches
Critical Section Area	11.859	in ²
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	100%	
Connection Strength	929	kips
Compression Efficiency	100%	
Uniaxial Bend Rating	64.0	° / 100 ft
Min Make Up Torque	10,000	ft-lbs
Yield Torque	42,500	ft-lbs



v1.1

1/4/2019

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.



SEMI
PREMIUMCONNECTIONS
FIELD TESTED. FIELD PROVEN.


Torque Data Sheet - Precision Connections BK-FX

7 in. 29 lb/ft P-110 with 7.875 in. Coupling OD

Min Make Up Torque	10,000	ft-lbs
Max Make Up Torque	31,900	ft-lbs
Optimum Torque	15,300	ft-lbs

Max Operating Torque	36,150	ft-lbs
Yield Torque	42,500	ft-lbs

Representative Torque Turn Graph



v1.1

1/4/2019