





9.625 in. 53.5 lb/ft Q-125 with 10.625 in. Coupling OD

Pipe Body

| | | |
|-----------------------------|---------|---------------------|
| Nominal OD | 9.625 | inches |
| Nominal Weight | 53.50 | lb/ft |
| Wall Thickness | 0.545 | inches |
| Plain End Weight | 52.85 | lb/ft |
| Drift | 8.500 | inches |
| Nominal ID | 8.535 | inches |
| Grade | Q-125 | |
| Min Yield | 125,000 | lbf/in ² |
| Min Tensile | 135,000 | lbf/in ² |
| Critical Section Area | 15.546 | in ² |
| Pipe Body Yield Strength | 1943 | kips |
| Min Internal Yield Pressure | 12,390 | psi |
| Collapse Pressure | 8,440 | psi |

Connection

| | | |
|--------------------------|---------|----------------------------------------------------------------------------------------------|
| Coupling OD | 10.625 | inches |
| Coupling Length | 12.088 | inches |
| Make Up Loss | 5.731 | inches |
| Critical Section Area | 15.546 | in ² |
| Internal Pressure Rating | 100% | |
| External Pressure Rating | 100% | |
| Tension Efficiency | 100% | |
| Connection Strength | 1943 | kips |
| Compression Efficiency | 100% | |
| Uniaxial Bend Rating | 53.9 | ° / 100 ft |
| Min Make Up Torque | 10,000 | ft-lbs  |
| Yield Torque | 101,150 | ft-lbs  |



Torque Data Sheet - HOSS

9.625 in. 53.5 lb/ft Q-125 with 10.625 in. Coupling OD

| | | | |
|--------------------|---------------|----------------------|----------------|
| Min Make Up Torque | 10,000 ft-lbs | Max Operating Torque | 85,950 ft-lbs |
| Max Make Up Torque | 75,850 ft-lbs | Yield Torque | 101,150 ft-lbs |
| Optimum Torque | 20,000 ft-lbs | | |

Representative Torque Turn Graph

