



HYDRA 5.5in. x 17 lb/ft L-80 Flush Joint

Pipe Body

Nominal OD	5.500	inches
Nominal Weight	17.00	lb/ft
Wall Thickness	0.304	inches
Plain End Weight	16.87	lb/ft
Standard Drift	4.767	inches
Nominal ID	4.892	inches
Grade	L-80	
Min Yield	80,000	lbf/in ²
Min Tensile	95,000	lbf/in ²
Critical Section Area	4.962	in ²
Pipe Body Yield Strength	397	kips
Min Internal Yield Pressure	7,740	psi
Collapse Pressure	6,290	psi

Connection

Connection OD	5.500	inches
Make Up Loss	4.463	inches
Critical Section Area	2.977	in ²
Internal Pressure Rating	6,190	psi
External Pressure Rating	6,290	psi
Tension Efficiency	60%	
Connection Strength	238	kips
Compression Efficiency	238	kips
Uniaxial Bend Rating	42	° / 100 ft
Reference Depth	9,413	Ft.
Optimal Make Up Torque	5,525	ft-lbs 
Min	4,650	ft-lbs 
Max	6,400	ft-lbs

v1.0

5/9/2019

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.

The performance properties in these data tables are calculated per API 5C3. Calculations are based on nominal wall thickness. Loads do not reflect a design safety factor for walls thinner than nominal or other defects. Reference Depth = Connection Strength / (PE Wt./Ft)*(1.5). Reference Depth includes a 1.5 design factor. However, it does not consider bending, temperature, buoyancy or other load considerations.



Torque Data Sheet - HYDRA

HYDRA 5.5in. x 17 lb/ft L-80 Flush Joint

Min Make Up Torque	4,650	ft-lbs
Max Make Up Torque	6,400	ft-lbs
Optimum Torque	5,525	ft-lbs

Nom Shoulder Torque	800	ft-lbs
---------------------	-----	--------

