

HYDRA 5.5in. x 20 lb/ft P-110 Flush Joint

Pipe Body

Nominal OD	5.500	inches
Nominal Weight	20.00	lb/ft
Wall Thickness	0.361	inches
Plain End Weight	19.81	lb/ft
Standard Drift	4.653	inches
Nominal ID	4.778	inches
Grade	P-110	
Min Yield	110,000	lb/in ²
Min Tensile	125,000	lb/in ²
Critical Section Area	5.828	in ²
Pipe Body Yield Strength	641	kips
Min Internal Yield Pressure	12,640	psi
Collapse Pressure	11,100	psi

Connection

Connection OD	5.500	inches
Make Up Loss	4.738	inches
Critical Section Area	3.497	in ²
Internal Pressure Rating	10,110	psi
External Pressure Rating	11,100	psi
Tension Efficiency	60%	
Connection Strength	385	kips
Compression Efficiency	385	kips
Uniaxial Bend Rating	58	° / 100 ft
Reference Depth	12,943	Ft.
Optimal Make Up Torque	8,700	ft-lbs
Min	7,175	ft-lbs
Max	10,225	ft-lbs

v1.0

4/2/2019

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.

The performance properties in these data tables are calculated per API 5C3. Calculations are based on nominal wall thickness. Loads do not reflect a design safety factor for walls thinner than nominal or other defects. Reference Depth = Connection Strength / (PE Wt./Ft)*(1.5). Reference Depth includes a 1.5 design factor. However, it does not consider bending, temperature, buoyancy or other load considerations.