



Blanking Dimensions

OG™ PREMIUM FLUSH 3.5in. x 9.2 lb/ft



Pipe Body

Nominal OD	3.500	inches	Plain End Weight	8.81	lb/ft
Nominal Weight	9.20	lb/ft	Drift	2.867	inches
Wall Thickness	0.254	inches	Nominal ID	2.992	inches

Pin Blanking Dimensions



Pin OD Max	3.535	inches	Pin Minimum Length	5.500	inches
Pin OD Min	3.500	inches	Additional Recut Length	2.500	inches
Pin ID	2.955 ± .010	inches			

Box Blanking Dimensions



Box OD Max	3.535	inches	Box Minimum Length	5.500	inches
Box OD Min	3.500	inches	Additional Recut Length	2.000	inches
Box ID	2.992 ± .016	inches			

OD and ID transitions to be tapered at 30 degrees to avoid hangups and no drift situations



Blanking Dimensions

OG™ PREMIUM FLUSH 4in. x 11 lb/ft



Pipe Body

Nominal OD	4.000	inches	Plain End Weight	10.46	lb/ft
Nominal Weight	11.00	lb/ft	Drift	3.351	inches
Wall Thickness	0.262	inches	Nominal ID	3.476	inches

Pin Blanking Dimensions



Pin OD Max	4.040	inches	Pin Minimum Length	6.250	inches
Pin OD Min	4.000	inches	Additional Recut Length	3.000	inches
Pin ID	3.439 ± .010	inches			

Box Blanking Dimensions



Box OD Max	4.040	inches	Box Minimum Length	6.250	inches
Box OD Min	4.000	inches	Additional Recut Length	2.250	inches
Box ID	3.476 ± .016	inches			

OD and ID transitions to be tapered at 30 degrees to avoid hangups and no drift situations

v1.0

8/8/2019



Blanking Dimensions

OG™ PREMIUM FLUSH 4in. x 11.6 lb/ft



Pipe Body

Nominal OD	4.000	inches	Plain End Weight	11.34	lb/ft
Nominal Weight	11.60	lb/ft	Drift	3.303	inches
Wall Thickness	0.286	inches	Nominal ID	3.428	inches

Pin Blanking Dimensions



Pin OD Max	4.040	inches	Pin Minimum Length	6.500	inches
Pin OD Min	4.000	inches	Additional Recut Length	3.000	inches
Pin ID	3.391 ± .010	inches			

Box Blanking Dimensions



Box OD Max	4.040	inches	Box Minimum Length	6.500	inches
Box OD Min	4.000	inches	Additional Recut Length	2.500	inches
Box ID	3.428 ± .016	inches			

OD and ID transitions to be tapered at 30 degrees to avoid hangups and no drift situations

v1.0

8/8/2019



Blanking Dimensions

OG™ PREMIUM FLUSH 4.5in. x 11.6 lb/ft



Pipe Body

Nominal OD	4.500	inches	Plain End Weight	11.35	lb/ft
Nominal Weight	11.60	lb/ft	Drift	3.875	inches
Wall Thickness	0.250	inches	Nominal ID	4.000	inches

Pin Blanking Dimensions



Pin OD Max	4.545	inches	Pin Minimum Length	5.500	inches
Pin OD Min	4.500	inches	Additional Recut Length	2.750	inches
Pin ID	3.963 ± .010	inches			

Box Blanking Dimensions



Box OD Max	4.545	inches	Box Minimum Length	5.500	inches
Box OD Min	4.500	inches	Additional Recut Length	2.000	inches
Box ID	4.000 ± .016	inches			

OD and ID transitions to be tapered at 30 degrees to avoid hangups and no drift situations



Blanking Dimensions

OG™ PREMIUM FLUSH 4.5in. x 13.5 lb/ft



Pipe Body

Nominal OD	4.500	inches	Plain End Weight	13.04	lb/ft
Nominal Weight	13.50	lb/ft	Drift	3.795	inches
Wall Thickness	0.290	inches	Nominal ID	3.920	inches

Pin Blanking Dimensions



Pin OD Max	4.545	inches	Pin Minimum Length	6.500	inches
Pin OD Min	4.500	inches	Additional Recut Length	3.000	inches
Pin ID	3.883 ± .010	inches			

Box Blanking Dimensions



Box OD Max	4.545	inches	Box Minimum Length	6.500	inches
Box OD Min	4.500	inches	Additional Recut Length	2.250	inches
Box ID	3.920 ± .016	inches			

OD and ID transitions to be tapered at 30 degrees to avoid hangups and no drift situations

v1.0

8/8/2019



Blanking Dimensions

OG™ PREMIUM FLUSH 5.5in. x 17 lb/ft



Pipe Body

Nominal OD	5.500	inches	Plain End Weight	16.87	lb/ft
Nominal Weight	17.00	lb/ft	Drift	4.767	inches
Wall Thickness	0.304	inches	Nominal ID	4.892	inches

Pin Blanking Dimensions



Pin OD Max	5.555	inches	Pin Minimum Length	6.500	inches
Pin OD Min	5.500	inches	Additional Recut Length	3.000	inches
Pin ID	4.855 ± .010	inches			

Box Blanking Dimensions



Box OD Max	5.555	inches	Box Minimum Length	6.500	inches
Box OD Min	5.500	inches	Additional Recut Length	2.250	inches
Box ID	4.892 ± .016	inches			

OD and ID transitions to be tapered at 30 degrees to avoid hangups and no drift situations



Blanking Dimensions

OG™ PREMIUM FLUSH 5.5in. x 20 lb/ft



Pipe Body

Nominal OD	5.500	inches	Plain End Weight	19.81	lb/ft
Nominal Weight	20.00	lb/ft	Drift	4.653	inches
Wall Thickness	0.361	inches	Nominal ID	4.778	inches

Pin Blanking Dimensions



Pin OD Max	5.555	inches	Pin Minimum Length	7.000	inches
Pin OD Min	5.500	inches	Additional Recut Length	3.250	inches
Pin ID	4.741 ± .010	inches			

Box Blanking Dimensions



Box OD Max	5.555	inches	Box Minimum Length	7.000	inches
Box OD Min	5.500	inches	Additional Recut Length	2.500	inches
Box ID	4.778 ± .016	inches			

OD and ID transitions to be tapered at 30 degrees to avoid hangups and no drift situations

v1.0

8/8/2019



Blanking Dimensions

OG™ PREMIUM FLUSH 7.625in. x 29.7 lb/ft



OG PREMIUM FLUSH

Pipe Body

Nominal OD	7.625	inches	Plain End Weight	29.04	lb/ft
Nominal Weight	29.70	lb/ft	Drift	6.750	inches
Wall Thickness	0.375	inches	Nominal ID	6.875	inches

Pin Blanking Dimensions



Pin OD Max	7.701	inches	Pin Minimum Length	6.000	inches
Pin OD Min	7.625	inches	Additional Recut Length	3.000	inches
Pin ID	6.838 ± .010	inches			

Box Blanking Dimensions



Box OD Max	7.701	inches	Box Minimum Length	6.000	inches
Box OD Min	7.625	inches	Additional Recut Length	2.250	inches
Box ID	6.875 ± .016	inches			

OD and ID transitions to be tapered at 30 degrees to avoid hangups and no drift situations

v1.0

8/8/2019



Blanking Dimensions

OG™ PREMIUM FLUSH 7.625in. x 33.7 lb/ft



OG PREMIUM FLUSH

Pipe Body

Nominal OD	7.625	inches	Plain End Weight	33.04	lb/ft
Nominal Weight	33.70	lb/ft	Drift	6.640	inches
Wall Thickness	0.430	inches	Nominal ID	6.765	inches

Pin Blanking Dimensions



Pin OD Max	7.701	inches	Pin Minimum Length	7.000	inches
Pin OD Min	7.625	inches	Additional Recut Length	3.500	inches
Pin ID	6.728 ± .010	inches			

Box Blanking Dimensions



Box OD Max	7.701	inches	Box Minimum Length	7.000	inches
Box OD Min	7.625	inches	Additional Recut Length	2.750	inches
Box ID	6.765 ± .016	inches			

OD and ID transitions to be tapered at 30 degrees to avoid hangups and no drift situations

v1.0

8/8/2019