

## OG™ PREMIUM FLUSH 4.5in. x 13.5 lb/ft L-80



### Pipe Body

Nominal OD	4.500	inches
Nominal Weight	13.50	lb/ft
Wall Thickness	0.290	inches
Plain End Weight	13.04	lb/ft
Standard Drift	3.795	inches
Nominal ID	3.920	inches
Grade	L-80	
Min Yield	80,000	lb/in <sup>2</sup>
Min Tensile	95,000	lb/in <sup>2</sup>
Critical Section Area	3.836	in <sup>2</sup>
Pipe Body Yield Strength	307	kips
Min Internal Yield Pressure	9,020	psi
Collapse Pressure	8,540	psi

### Connection

Connection OD	4.500	inches
Connection ID	3.883	inches
Make Up Loss	5.834	inches
Critical Section Area	2.416	in <sup>2</sup>
Internal / External Pressure Rating	100%	of Pipe
Internal Pressure	9,020	
External Pressure	8,540	
Tension Efficiency	63%	193 kips
Compression Efficiency	63%	193 kips
Uniaxial Bend Rating	51	° / 100 ft
Optimal Make Up Torque	2,327	ft-lbs
Min	2,090	ft-lbs
Max	2,560	ft-lbs

v1.0

9/9/2019

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.

The performance properties in these data tables are calculated per API 5C3. Calculations are based on nominal wall thickness. Loads do not reflect a design safety factor for walls thinner than nominal or other defects.



## Torque Data Sheet - OG™ PREMIUM FLUSH



OG™ PREMIUM FLUSH 4.5in. x 13.5 lb/ft L-80

Min Make Up Torque	2,090	ft-lbs
Max Make Up Torque	2,560	ft-lbs
Optimum Torque	2,327	ft-lbs

Nom Shoulder Torque	1,200	ft-lbs
---------------------	-------	--------

