

## Precision Connections BK-HT


5.5 in. 26 lb/ft P110 EB with 6.3 in. Coupling OD

### Pipe Body

Nominal OD	5.500	inches
Nominal Weight	26.00	lb/ft
Wall Thickness	0.476	inches
Plain End Weight	25.55	lb/ft
Drift	4.545	inches
Nominal ID	4.548	inches
Grade	P110 EB	
Min Yield	125,000	lbf/in <sup>2</sup>
Min Tensile	130,000	lbf/in <sup>2</sup>
Critical Section Area	7.513	in <sup>2</sup>
Pipe Body Yield Strength	939	kips
Min Internal Yield Pressure	18,930	psi
Collapse Pressure	19,760	psi

### Connection

Coupling OD	6.300	inches
Coupling Length	8.250	inches
Make Up Loss	4.125	inches
Critical Section Area	8.456	in <sup>2</sup>
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	100%	
Connection Strength	939	kips
Compression Efficiency	100%	
Uniaxial Bend Rating	91.0	° / 100 ft
Min Make Up Torque	10,000	ft-lbs
Yield Torque	47,750	ft-lbs



## Torque Data Sheet - Precision Connections BK-HT

5.5 in. 26 lb/ft P110 EB with 6.3 in. Coupling OD

Min Make Up Torque	10,000	ft-lbs	Max Operating Torque	40,550	ft-lbs
Max Make Up Torque	35,800	ft-lbs	Yield Torque	47,750	ft-lbs
Optimum Torque	17,200	ft-lbs			

**Representative Torque Turn Graph**

