



## 6 in. 24 lb/ft P-110 with 6.875 in. Coupling OD

### Pipe Body

Nominal OD	6.000	inches
Nominal Weight	24.00	lb/ft
Wall Thickness	0.4	inches
Plain End Weight	23.95	lb/ft
Drift	5.075	inches
Nominal ID	5.200	inches
Grade	P-110	
Min Yield	110,000	lbf/in <sup>2</sup>
Min Tensile	125,000	lbf/in <sup>2</sup>
Critical Section Area	7.037	in <sup>2</sup>
Pipe Body Yield Strength	774	kips
Min Internal Yield Pressure	12,830	psi
Collapse Pressure	11,460	psi

### Connection

Coupling OD	6.875	inches
Coupling Length	11.088	inches
Make Up Loss	5.232	inches
Critical Section Area	7.037	in <sup>2</sup>
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	100%	
Connection Strength	774	kips
Compression Efficiency	100%	
Uniaxial Bend Rating	73.3	° / 100 ft
Min Make Up Torque	6,750	ft-lbs
Yield Torque	26,000	ft-lbs





## Torque Data Sheet - HOSS

### 6 in. 24 lb/ft P-110 with 6.875 in. Coupling OD

Min Make Up Torque	6,750	ft-lbs	Max Operating Torque	22,100	ft-lbs
Max Make Up Torque	19,500	ft-lbs	Yield Torque	26,000	ft-lbs
Optimum Torque	9,350	ft-lbs			

Representative Torque Turn Graph

