





9.625 in. 40 lb/ft P110 EB with 10.625 in. Coupling OD

Pipe Body

Nominal OD	9.625	inches
Nominal Weight	40.00	lb/ft
Wall Thickness	0.395	inches
Plain End Weight	38.97	lb/ft
Drift	8.750	inches
Nominal ID	8.835	inches
<hr/>		
Grade	P110 EB	
Min Yield	125,000	lbf/in ²
Min Tensile	135,000	lbf/in ²
Critical Section Area	11.454	in ²
Pipe Body Yield Strength	1432	kips
Min Internal Yield Pressure	8,980	psi
Collapse Pressure	4,230	psi

Connection

Coupling OD	10.625	inches
Coupling Length	12.088	inches
Make Up Loss	5.731	inches
Critical Section Area	11.454	in ²
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	100%	
Connection Strength	1432	kips
Compression Efficiency	100%	
Uniaxial Bend Rating	53.9	° / 100 ft
Min Make Up Torque	10,000	ft-lbs 
Yield Torque	62,500	ft-lbs 



Torque Data Sheet - HOSS

9.625 in. 40 lb/ft P110 EB with 10.625 in. Coupling OD

Min Make Up Torque	10,000	ft-lbs	Max Operating Torque	53,150	ft-lbs
Max Make Up Torque	46,900	ft-lbs	Yield Torque	62,500	ft-lbs
Optimum Torque	20,000	ft-lbs			

Representative Torque Turn Graph

