





9.625 in. 43.5 lb/ft HC-P110 with 10.625 in. Coupling OD

Pipe Body

Nominal OD	9.625	inches
Nominal Weight	43.50	lb/ft
Wall Thickness	0.435	inches
Plain End Weight	42.73	lb/ft
Drift	8.599	inches
Nominal ID	8.755	inches
<hr/>		
Grade	HC-P110	
Min Yield	110,000	lbf/in ²
Min Tensile	125,000	lbf/in ²
Critical Section Area	12.559	in ²
Pipe Body Yield Strength	1381	kips
Min Internal Yield Pressure	8,700	psi
Collapse Pressure	5,440	psi

Connection

Coupling OD	10.625	inches
Coupling Length	12.088	inches
Make Up Loss	5.731	inches
Critical Section Area	12.559	in ²
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	100%	
Connection Strength	1381	kips
Compression Efficiency	100%	
Uniaxial Bend Rating	47.4	° / 100 ft
Min Make Up Torque	10,000	ft-lbs 
Yield Torque	64,350	ft-lbs 



Torque Data Sheet - HOSS

9.625 in. 43.5 lb/ft HC-P110 with 10.625 in. Coupling OD

Min Make Up Torque	10,000	ft-lbs	Max Operating Torque	54,700	ft-lbs
Max Make Up Torque	48,250	ft-lbs	Yield Torque	64,350	ft-lbs
Optimum Torque	20,000	ft-lbs			

Representative Torque Turn Graph

