



9.625 in. 47 lb/ft P110 EB with 10.625 in. Coupling OD

Pipe Body

| | | |
|-----------------------------|---------|---------------------|
| Nominal OD | 9.625 | inches |
| Nominal Weight | 47.00 | lb/ft |
| Wall Thickness | 0.472 | inches |
| Plain End Weight | 46.18 | lb/ft |
| Drift | 8.525 | inches |
| Nominal ID | 8.681 | inches |
| Grade | P110 EB | |
| Min Yield | 125,000 | lbf/in ² |
| Min Tensile | 135,000 | lbf/in ² |
| Critical Section Area | 13.572 | in ² |
| Pipe Body Yield Strength | 1697 | kips |
| Min Internal Yield Pressure | 10,730 | psi |
| Collapse Pressure | 6,660 | psi |

Connection

| | | |
|--------------------------|--------|--|
| Coupling OD | 10.625 | inches |
| Coupling Length | 12.088 | inches |
| Make Up Loss | 5.731 | inches |
| Critical Section Area | 13.572 | in ² |
| Internal Pressure Rating | 100% | |
| External Pressure Rating | 100% | |
| Tension Efficiency | 100% | |
| Connection Strength | 1697 | kips |
| Compression Efficiency | 100% | |
| Uniaxial Bend Rating | 53.9 | ° / 100 ft |
| Min Make Up Torque | 10,000 | ft-lbs  |
| Yield Torque | 82,400 | ft-lbs  |



Torque Data Sheet - HOSS

9.625 in. 47 lb/ft P110 EB with 10.625 in. Coupling OD

| | | | | | |
|--------------------|--------|--------|----------------------|--------|--------|
| Min Make Up Torque | 10,000 | ft-lbs | Max Operating Torque | 70,050 | ft-lbs |
| Max Make Up Torque | 61,800 | ft-lbs | Yield Torque | 82,400 | ft-lbs |
| Optimum Torque | 20,000 | ft-lbs | | | |

Representative Torque Turn Graph

