



9.875 in. 62.8 lb/ft P110 EB with 10.75 in. Coupling OD

Pipe Body

Nominal OD	9.875	inches
Nominal Weight	62.80	lb/ft
Wall Thickness	0.625	inches
Plain End Weight	61.80	lb/ft
Drift	8.469	inches
Nominal ID	8.625	inches
Grade	P110 EB	
Min Yield	125,000	lbf/in ²
Min Tensile	135,000	lbf/in ²
Critical Section Area	18.162	in ²
Pipe Body Yield Strength	2270	kips
Min Internal Yield Pressure	13,840	psi
Collapse Pressure	11,820	psi

Connection

Coupling OD	10.750	inches
Coupling Length	12.088	inches
Make Up Loss	5.731	inches
Critical Section Area	15.825	in ²
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	87%	
Connection Strength	1975	kips
Compression Efficiency	100%	
Uniaxial Bend Rating	53.3	° / 100 ft
Min Make Up Torque	10,000	ft-lbs
Yield Torque	92,600	ft-lbs





Torque Data Sheet - HOSS

9.875 in. 62.8 lb/ft P110 EB with 10.75 in. Coupling OD

Min Make Up Torque	10,000	ft-lbs	Max Operating Torque	78,700	ft-lbs
Max Make Up Torque	69,450	ft-lbs	Yield Torque	92,600	ft-lbs
Optimum Torque	20,000	ft-lbs			

Representative Torque Turn Graph

