

HYDRA 4.5in. x 15.1 lb/ft J-55 Flush Joint



Pipe Body

Nominal OD	4.500	inches
Nominal Weight	15.10	lb/ft
Wall Thickness	0.337	inches
Plain End Weight	15.00	lb/ft
Standard Drift	3.701	inches
Nominal ID	3.826	inches
Grade	J-55	
Min Yield	55,000	lb/in ²
Min Tensile	75,000	lb/in ²
Critical Section Area	4.407	in ²
Pipe Body Yield Strength	242	kips
Min Internal Yield Pressure	7,210	psi
Collapse Pressure	7,620	psi

Connection

Connection OD	4.500	inches
Make Up Loss	4.488	inches
Critical Section Area	2.644	in ²
Internal Pressure Rating	5,770	psi
External Pressure Rating	7,620	psi
Tension Efficiency	60%	
Connection Strength	145	kips
Compression Efficiency	145	kips
Uniaxial Bend Rating	35	° / 100 ft
Reference Depth	6,453	Ft.
Optimal Make Up Torque	2,838	ft-lbs
Min	2,363	ft-lbs
Max	3,300	ft-lbs

v1.0

12/12/2019

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.

The performance properties in these data tables are calculated per API 5C3. Calculations are based on nominal wall thickness. Loads do not reflect a design safety factor for walls thinner than nominal or other defects. Reference Depth = Connection Strength/ (PE Wt./Ft)*(1.5). Reference Depth includes a 1.5 design factor. However, it does not consider bending, temperature, buoyancy or other load considerations.



Torque Data Sheet - HYDRA

HYDRA 4.5in. x 15.1 lb/ft J-55 Flush Joint

Min Make Up Torque	2,363	ft-lbs	Nom Shoulder Torque	1,100	ft-lbs
Max Make Up Torque	3,300	ft-lbs	Max Operating	5,250	ft-lbs
Optimum Torque	2,838	ft-lbs	Yield	6,450	ft-lbs

