

## HYDRA 5.5in. x 20 lb/ft J-55 Flush Joint



### Pipe Body

Nominal OD	5.500	inches
Nominal Weight	20.00	lb/ft
Wall Thickness	0.361	inches
Plain End Weight	19.83	lb/ft
Standard Drift	4.653	inches
Nominal ID	4.778	inches
Grade	J-55	
Min Yield	55,000	lb/in <sup>2</sup>
Min Tensile	75,000	lb/in <sup>2</sup>
Critical Section Area	5.828	in <sup>2</sup>
Pipe Body Yield Strength	321	kips
Min Internal Yield Pressure	6,320	psi
Collapse Pressure	6,620	psi

### Connection

Connection OD	5.500	inches
Make Up Loss	4.738	inches
Critical Section Area	3.497	in <sup>2</sup>
Internal Pressure Rating	5,050	psi
External Pressure Rating	6,620	psi
Tension Efficiency	60%	
Connection Strength	193	kips
Compression Efficiency	193	kips
Uniaxial Bend Rating	29	° / 100 ft
Reference Depth	6,475	Ft.
Optimal Make Up Torque	4,350	ft-lbs
Min	3,588	ft-lbs
Max	5,113	ft-lbs

v1.0

12/12/2019

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.

The performance properties in these data tables are calculated per API 5C3. Calculations are based on nominal wall thickness. Loads do not reflect a design safety factor for walls thinner than nominal or other defects. Reference Depth = Connection Strength/ (PE Wt./Ft)\*(1.5). Reference Depth includes a 1.5 design factor. However, it does not consider bending, temperature, buoyancy or other load considerations.



## Torque Data Sheet - HYDRA

HYDRA 5.5in. x 20 lb/ft J-55 Flush Joint

Min Make Up Torque	3,588	ft-lbs
Max Make Up Torque	5,113	ft-lbs
Optimum Torque	4,350	ft-lbs

Nom Shoulder Torque	800	ft-lbs
Max Operating	6,450	ft-lbs
Yield	10,500	ft-lbs

