



## HYDRA 7in. x 29 lb/ft J-55 Flush Joint



### Pipe Body

Nominal OD	7.000	inches
Nominal Weight	29.00	lb/ft
Wall Thickness	0.408	inches
Plain End Weight	28.75	lb/ft
Standard Drift	6.125	inches
Nominal ID	6.184	inches
Grade	J-55	
Min Yield	55,000	lb/in <sup>2</sup>
Min Tensile	75,000	lb/in <sup>2</sup>
Critical Section Area	8.449	in <sup>2</sup>
Pipe Body Yield Strength	465	kips
Min Internal Yield Pressure	5,610	psi
Collapse Pressure	5,410	psi

### Connection

Connection OD	7.000	inches
Make Up Loss	4.140	inches
Critical Section Area	5.070	in <sup>2</sup>
Internal Pressure Rating	4,490	psi
External Pressure Rating	5,410	psi
Tension Efficiency	60%	
Connection Strength	279	kips
Compression Efficiency	279	kips
Uniaxial Bend Rating	23	° / 100 ft
Reference Depth	6,470	Ft.
Optimal Make Up Torque	7,300	ft-lbs 
Min	5,788	ft-lbs 
Max	8,825	ft-lbs

v1.0

12/12/2019

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.

The performance properties in these data tables are calculated per API 5C3. Calculations are based on nominal wall thickness. Loads do not reflect a design safety factor for walls thinner than nominal or other defects. Reference Depth = Connection Strength / (PE Wt./Ft)\*(1.5). Reference Depth includes a 1.5 design factor. However, it does not consider bending, temperature, buoyancy or other load considerations.

## Torque Data Sheet - HYDRA

HYDRA 7in. x 29 lb/ft J-55 Flush Joint

Min Make Up Torque	5,788	ft-lbs	Nom Shoulder Torque	990	ft-lbs
Max Make Up Torque	8,825	ft-lbs	Max Operating	13,850	ft-lbs
Optimum Torque	7,300	ft-lbs	Yield	17,350	ft-lbs

