



HYDRA 7.625in. x 33.7 lb/ft P110 EB Flush Joint



Pipe Body

Nominal OD	7.625	inches
Nominal Weight	33.70	lb/ft
Wall Thickness	0.430	inches
Plain End Weight	33.07	lb/ft
Standard Drift	6.640	inches
Nominal ID	6.765	inches
Grade	P110 EB	
Min Yield	125,000	lb/in ²
Min Tensile	130,000	lb/in ²
Critical Section Area	9.720	in ²
Pipe Body Yield Strength	1215	kips
Min Internal Yield Pressure	12,340	psi
Collapse Pressure	0	psi

Connection

Connection OD	7.625	inches
Make Up Loss	4.450	inches
Critical Section Area	5.832	in ²
Internal Pressure Rating	9,870	psi
External Pressure Rating	0	psi
Tension Efficiency	60%	
Connection Strength	729	kips
Compression Efficiency	729	kips
Uniaxial Bend Rating	47	° / 100 ft
Reference Depth	14,696	Ft.
Optimal Make Up Torque	20,170	ft-lbs 
Min	16,023	ft-lbs 
Max	24,318	ft-lbs

v1.0

12/12/2019

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.

The performance properties in these data tables are calculated per API 5C3. Calculations are based on nominal wall thickness. Loads do not reflect a design safety factor for walls thinner than nominal or other defects. Reference Depth = Connection Strength/ (PE Wt./Ft)*(1.5). Reference Depth includes a 1.5 design factor. However, it does not consider bending, temperature, buoyancy or other load considerations.

Torque Data Sheet - HYDRA

HYDRA 7.625in. x 33.7 lb/ft P110 EB Flush Joint

Min Make Up Torque	16,023	ft-lbs	Nom Shoulder Torque	1,260	ft-lbs
Max Make Up Torque	24,318	ft-lbs	Max Operating	38,182	ft-lbs
Optimum Torque	20,170	ft-lbs	Yield	47,727	ft-lbs

