

OG™ PREMIUM FLUSH 5in. x 18 lb/ft P-110



Pipe Body

Nominal OD	5.000	inches
Nominal Weight	18.00	lb/ft
Wall Thickness	0.362	inches
Plain End Weight	17.93	lb/ft
Standard Drift	4.151	inches
Nominal ID	4.276	inches
Grade	P-110	
Min Yield	110,000	lbf/in ²
Min Tensile	125,000	lbf/in ²
Critical Section Area	5.275	in ²
Pipe Body Yield Strength	580	kips
Min Internal Yield Pressure	13,940	psi
Collapse Pressure	13,470	psi

Connection

Connection OD	5.000	inches
Connection ID	4.239	inches
Make Up Loss	5.699	inches
Critical Section Area	3.428	in ²
Internal / External Pressure Rating	100% of Pipe	
Internal Pressure	13,940	
External Pressure	13,470	
Tension Efficiency	65%	377 kips
Compression Efficiency	65%	377 kips
Uniaxial Bend Rating	66	° / 100 ft
Optimal Make Up Torque	4,750	ft-lbs
Min	4,280	ft-lbs
Max	5,230	ft-lbs

v1.0

9/19/2019

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.

The performance properties in these data tables are calculated per API 5C3. Calculations are based on nominal wall thickness. Loads do not reflect a design safety factor for walls thinner than nominal or other defects.



Torque Data Sheet - OG™ PREMIUM FLUSH



OG™ PREMIUM FLUSH 5in. x 18 lb/ft P-110

Min Make Up Torque	4,280	ft-lbs	Nom Shoulder Torque	1,700	ft-lbs
Max Make Up Torque	5,230	ft-lbs			
Optimum Torque	4,750	ft-lbs			

