

HYDRA 4.5in. x 11.6 lb/ft HC-P110 Flush Joint



Pipe Body

Nominal OD	4.500	inches
Nominal Weight	11.60	lb/ft
Wall Thickness	0.250	inches
Plain End Weight	11.36	lb/ft
Standard Drift	3.875	inches
Nominal ID	4.000	inches
Grade	HC-P110	
Min Yield	110,000	lb/in ²
Min Tensile	125,000	lb/in ²
Critical Section Area	3.338	in ²
Pipe Body Yield Strength	367	kips
Min Internal Yield Pressure	10,690	psi
Collapse Pressure	8,830	psi

Connection

Connection OD	4.500	inches
Make Up Loss	4.038	inches
Critical Section Area	2.003	in ²
Internal Pressure Rating	8,560	psi
External Pressure Rating	8,830	psi
Tension Efficiency	60%	
Connection Strength	220	kips
Compression Efficiency	220	kips
Uniaxial Bend Rating	70	° / 100 ft
Reference Depth	12,923	Ft.
Optimal Make Up Torque	3,700	ft-lbs
Min	3,075	ft-lbs
Max	4,325	ft-lbs

v1.0

2/5/2020

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.

The performance properties in these data tables are calculated per API 5C3. Calculations are based on nominal wall thickness. Loads do not reflect a design safety factor for walls thinner than nominal or other defects. Reference Depth = Connection Strength / (PE Wt./Ft)*(1.5). Reference Depth includes a 1.5 design factor. However, it does not consider bending, temperature, buoyancy or other load considerations.

Torque Data Sheet - HYDRA

HYDRA 4.5in. x 11.6 lb/ft HC-P110 Flush Joint

Min Make Up Torque	3,075	ft-lbs	Nom Shoulder Torque	500	ft-lbs
Max Make Up Torque	4,325	ft-lbs	Max Operating	6,500	ft-lbs
Optimum Torque	3,700	ft-lbs	Yield	7,800	ft-lbs

