

## HYDRA 7in. x 23 lb/ft HC-L80 Flush Joint




### HYDRA

#### Pipe Body

Nominal OD	7.000	inches
Nominal Weight	23.00	lb/ft
Wall Thickness	0.317	inches
Plain End Weight	22.65	lb/ft
Standard Drift	6.250	inches
Nominal ID	6.366	inches
Grade	HC-L80	
Min Yield	80,000	lb/in <sup>2</sup>
Min Tensile	95,000	lb/in <sup>2</sup>
Critical Section Area	6.655	in <sup>2</sup>
Pipe Body Yield Strength	532	kips
Min Internal Yield Pressure	6,340	psi
Collapse Pressure	4,850	psi

#### Connection

Connection OD	7.000	inches
Make Up Loss	3.780	inches
Critical Section Area	3.993	in <sup>2</sup>
Internal Pressure Rating	5,070	psi
External Pressure Rating	4,850	psi
Tension Efficiency	60%	
Connection Strength	319	kips
Compression Efficiency	319	kips
Uniaxial Bend Rating	32	° / 100 ft
Reference Depth	9,395	Ft.
Optimal Make Up Torque	7,655	ft-lbs
Min	6,036	ft-lbs
Max	9,255	ft-lbs



v1.0

2/5/2020

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.

The performance properties in these data tables are calculated per API 5C3. Calculations are based on nominal wall thickness. Loads do not reflect a design safety factor for walls thinner than nominal or other defects. Reference Depth = Connection Strength / (PE Wt./Ft)\*(1.5). Reference Depth includes a 1.5 design factor. However, it does not consider bending, temperature, buoyancy or other load considerations.



## Torque Data Sheet - HYDRA

HYDRA 7in. x 23 lb/ft HC-L80 Flush Joint

Min Make Up Torque	6,036	ft-lbs	Nom Shoulder Torque	670	ft-lbs
Max Make Up Torque	9,255	ft-lbs	Max Operating	14,764	ft-lbs
Optimum Torque	7,655	ft-lbs	Yield	18,473	ft-lbs

