

HYDRA 7in. x 23 lb/ft HC-P110 Flush Joint



HYDRA

Pipe Body

Nominal OD	7.000	inches
Nominal Weight	23.00	lb/ft
Wall Thickness	0.317	inches
Plain End Weight	22.65	lb/ft
Standard Drift	6.250	inches
Nominal ID	6.366	inches
Grade	HC-P110	
Min Yield	110,000	lb/in ²
Min Tensile	125,000	lb/in ²
Critical Section Area	6.655	in ²
Pipe Body Yield Strength	732	kips
Min Internal Yield Pressure	8,720	psi
Collapse Pressure	5,470	psi

Connection

Connection OD	7.000	inches
Make Up Loss	3.780	inches
Critical Section Area	3.993	in ²
Internal Pressure Rating	6,970	psi
External Pressure Rating	5,470	psi
Tension Efficiency	60%	
Connection Strength	439	kips
Compression Efficiency	439	kips
Uniaxial Bend Rating	45	° / 100 ft
Reference Depth	12,927	Ft.
Optimal Make Up Torque	10,525	ft-lbs
Min	8,300	ft-lbs
Max	12,725	ft-lbs

v1.0

2/5/2020

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.

The performance properties in these data tables are calculated per API 5C3. Calculations are based on nominal wall thickness. Loads do not reflect a design safety factor for walls thinner than nominal or other defects. Reference Depth = Connection Strength / (PE Wt./Ft)*(1.5). Reference Depth includes a 1.5 design factor. However, it does not consider bending, temperature, buoyancy or other load considerations.

Torque Data Sheet - HYDRA

HYDRA 7in. x 23 lb/ft HC-P110 Flush Joint

Min Make Up Torque	8,300	ft-lbs	Nom Shoulder Torque	670	ft-lbs
Max Make Up Torque	12,725	ft-lbs	Max Operating	20,300	ft-lbs
Optimum Torque	10,525	ft-lbs	Yield	25,400	ft-lbs

