



Precision Connections BK-HT

4.5 in. 13.5 lb/ft P110 EB with 5.25 in. Coupling OD

Pipe Body

Nominal OD	4.500	inches
Nominal Weight	13.50	lb/ft
Wall Thickness	0.29	inches
Plain End Weight	13.05	lb/ft
Drift	3.795	inches
Nominal ID	3.920	inches
Grade	P110 EB	
Min Yield	125,000	lbf/in ²
Min Tensile	130,000	lbf/in ²
Critical Section Area	3.836	in ²
Pipe Body Yield Strength	479	kips
Min Internal Yield Pressure	14,100	psi
Collapse Pressure	12,290	psi

Connection

Coupling OD	5.250	inches
Coupling Length	7.875	inches
Make Up Loss	3.938	inches
Coupling Critical Area	6.484	in ²
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	100%	
Connection Strength	479	kips
Compression Efficiency	100%	
Joint Strength	467	kips
Uniaxial Bend Rating	109.2	° / 100 ft
Min Make Up Torque	4,450	ft-lbs 
Yield Torque	17,050	ft-lbs 



Torque Data Sheet - Precision Connections BK-HT

4.5 in. 13.5 lb/ft P110 EB with 5.25 in. Coupling OD

Min Make Up Torque 4,450 ft-lbs

Max Make Up Torque 12,800 ft-lbs

Optimum Torque 6,150 ft-lbs

Max Operating Torque 14,500 ft-lbs

Yield Torque 17,050 ft-lbs

Representative Torque Turn Graph

