



Precision Connections BK

9.625 in. 47 lb/ft P110 EB with 10.625 in. Coupling OD

Pipe Body

Nominal OD	9.625	inches
Nominal Weight	47.00	lb/ft
Wall Thickness	0.472	inches
Plain End Weight	46.18	lb/ft
Drift	8.525	inches
Nominal ID	8.681	inches
Grade	P110 EB	
Min Yield	125,000	lbf/in ²
Min Tensile	130,000	lbf/in ²
Critical Section Area	13.572	in ²
Pipe Body Yield Strength	1697	klps
Min Internal Yield Pressure	10,730	psi
Collapse Pressure	6,660	psi

Connection

Coupling OD	10.625	inches
Coupling Length	9.625	inches
Make Up Loss	4.813	inches
Coupling Critical Area	18.558	in ²
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	100%	
Connection Strength	1697	klps
Compression Efficiency	100%	
Joint Strength	1612	klps
Uniaxial Bend Rating	53.9	° / 100 ft
Min Make Up Torque	10,000	ft-lbs 
Yield Torque	111,500	ft-lbs 



Torque Data Sheet - Precision Connections BK

9.625 in. 47 lb/ft P110 EB with 10.625 in. Coupling OD

Min Make Up Torque 10,000 ft-lbs

Max Make Up Torque 83,600 ft-lbs

Optimum Torque 20,000 ft-lbs

Max Operating Torque 94,750 ft-lbs

Yield Torque 111,500 ft-lbs

Representative Torque Turn Graph

