





5.5 in. 26 lb/ft P-110 with 6.3 in. Coupling OD

Pipe Body

Nominal OD	5.500	inches
Nominal Weight	26.00	lb/ft
Wall Thickness	0.476	inches
Plain End Weight	25.56	lb/ft
Drift	4.423	inches
Nominal ID	4.548	inches
Grade	P-110	
Min Yield	110,000	lbf/in ²
Min Tensile	125,000	lbf/in ²
Critical Section Area	7.513	in ²
Pipe Body Yield Strength	826	kips
Min Internal Yield Pressure	16,660	psi
Collapse Pressure	17,390	psi

Connection

Coupling OD	6.300	inches
Coupling Length	10.713	inches
Make Up Loss	5.044	inches
Critical Section Area	7.513	in ²
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	100%	
Connection Strength	826	kips
Compression Efficiency	100%	
Uniaxial Bend Rating	80.0	° / 100 ft
Min Make Up Torque	8,050	ft-lbs 
Yield Torque	31,000	ft-lbs 



Torque Data Sheet - HOSS

5.5 in. 26 lb/ft P-110 with 6.3 in. Coupling OD

Min Make Up Torque	8,050	ft-lbs	Max Operating Torque	26,350	ft-lbs
Max Make Up Torque	23,250	ft-lbs	Yield Torque	31,000	ft-lbs
Optimum Torque	11,150	ft-lbs			

Representative Torque Turn Graph

