



InterLock Coupled 5.500 in. 17.00 lb/ft P110 HC

Pipe Body

Nominal OD	5.500	inches
Nominal Weight	17.00	lb/ft
Wall Thickness	0.304	inches
Plain End Weight	16.87	lb/ft
Drift	4.767	inches
Nominal ID	4.892	inches
Grade	P110 HC	
Min Yield	110,000	lb/in ²
Min Tensile	125,000	lb/in ²
Critical Section Area	4.962	in ²
Pipe Body Yield Strength	546	kips
Min Internal Yield Pressure	10,640	psi
Collapse Pressure	8,730	psi

Connection

Coupling OD	6.300	inches
Connection ID	4.892	inches
Coupling Length	8.691	inches
Make Up Loss	3.839	inches
Coupling CSA	8.855	in ²
Pin CSA	4.962	in ²
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	100%	
Connection Strength	546	kips
Compression Efficiency	100%	
Uniaxial Bend Rating	80.0	° / 100 ft

Make-up Values

Minimum Torque	16,000	ft-lbs
Optimum Torque	18,000	ft-lbs
Maximum Torque	20,000	ft-lbs
Operating Torque	32,000	ft-lbs
Yield Torque	40,000	ft-lbs



This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.