



InterLock SPSF 4.500 in. 12.60 lb/ft P110 EB

Pipe Body

Nominal OD	4.500	inches
Nominal Weight	12.60	lb/ft
Wall Thickness	0.271	inches
Plain End Weight	12.24	lb/ft
Drift	3.833	inches
Nominal ID	3.958	inches
Grade	P110 EB	
Min Yield	125,000	lb/in ²
Min Tensile	130,000	lb/in ²
Critical Section Area	3.600	in ²
Pipe Body Yield Strength	450	kips
Min Internal Yield Pressure	13,170	psi
Collapse Pressure	11,230	psi

Connection

Connection OD	4.776	inches
Connection ID	3.902	inches
Make Up Loss	3.763	inches
Critical Section Area	3.229	in ²
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	90%	
Compression Efficiency	90%	
Connection Strength	405	kips
Uniaxial Bend Rating	105.6	° / 100 ft

Make-up Values

Minimum Torque	10,000	ft-lbs
Optimum Torque	11,000	ft-lbs
Maximum Torque	12,000	ft-lbs
Operating Torque	18,400	ft-lbs
Yield Torque	23,000	ft-lbs



This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.