



## InterLock SPSF 4.500 in. 15.10 lb/ft P110 CY

### Pipe Body

|                             |         |                    |
|-----------------------------|---------|--------------------|
| Nominal OD                  | 4.500   | inches             |
| Nominal Weight              | 15.10   | lb/ft              |
| Wall Thickness              | 0.337   | inches             |
| Plain End Weight            | 14.98   | lb/ft              |
| Drift                       | 3.701   | inches             |
| Nominal ID                  | 3.826   | inches             |
| Grade                       | P110 CY |                    |
| Min Yield                   | 110,000 | lb/in <sup>2</sup> |
| Min Tensile                 | 125,000 | lb/in <sup>2</sup> |
| Critical Section Area       | 4.407   | in <sup>2</sup>    |
| Pipe Body Yield Strength    | 485     | kips               |
| Min Internal Yield Pressure | 14,410  | psi                |
| Collapse Pressure           | 14,340  | psi                |

### Connection

|                          |       |                 |
|--------------------------|-------|-----------------|
| Connection OD            | 4.826 | inches          |
| Connection ID            | 3.770 | inches          |
| Make Up Loss             | 4.588 | inches          |
| Critical Section Area    | 4.055 | in <sup>2</sup> |
| Internal Pressure Rating | 100%  |                 |
| External Pressure Rating | 100%  |                 |
| Tension Efficiency       | 90%   |                 |
| Compression Efficiency   | 90%   |                 |
| Connection Strength      | 437   | kips            |
| Uniaxial Bend Rating     | 104.5 | ° / 100 ft      |

### Make-up Values

|                  |        |        |
|------------------|--------|--------|
| Minimum Torque   | 10,000 | ft-lbs |
| Optimum Torque   | 11,000 | ft-lbs |
| Maximum Torque   | 12,000 | ft-lbs |
| Operating Torque | 24,650 | ft-lbs |
| Yield Torque     | 29,000 | ft-lbs |



This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.