



InterLock SPSF 5.000 in. 21.40 lb/ft P110 CY

Pipe Body

Nominal OD	5.000	inches
Nominal Weight	21.40	lb/ft
Wall Thickness	0.437	inches
Plain End Weight	21.30	lb/ft
Drift	4.001	inches
Nominal ID	4.126	inches
Grade	P110 CY	
Min Yield	110,000	lb/in ²
Min Tensile	125,000	lb/in ²
Critical Section Area	6.264	in ²
Pipe Body Yield Strength	689	kips
Min Internal Yield Pressure	16,820	psi
Collapse Pressure	17,550	psi

Connection

Connection OD	5.337	inches
Connection ID	4.107	inches
Make Up Loss	5.533	inches
Critical Section Area	5.645	in ²
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	90%	
Compression Efficiency	90%	
Connection Strength	620	kips
Uniaxial Bend Rating	94.5	° / 100 ft

Make-up Values

Minimum Torque	14,000	ft-lbs
Optimum Torque	15,000	ft-lbs
Maximum Torque	16,000	ft-lbs
Operating Torque	37,400	ft-lbs
Yield Torque	44,000	ft-lbs



This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.