



InterLock SPSF 5.500 in. 23.00 lb/ft P110 EB

Pipe Body

Nominal OD	5.500	inches
Nominal Weight	23.00	lb/ft
Wall Thickness	0.415	inches
Plain End Weight	22.54	lb/ft
Drift	4.545	inches
Nominal ID	4.670	inches
Grade	P110 EB	
Min Yield	125,000	lb/in ²
Min Tensile	130,000	lb/in ²
Critical Section Area	6.630	in ²
Pipe Body Yield Strength	829	kips
Min Internal Yield Pressure	16,500	psi
Collapse Pressure	16,470	psi

Connection

Connection OD	5.873	inches
Connection ID	4.614	inches
Make Up Loss	5.513	inches
Critical Section Area	6.130	in ²
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	90%	
Compression Efficiency	90%	
Connection Strength	746	kips
Uniaxial Bend Rating	85.9	° / 100 ft

Make-up Values

Minimum Torque	16,000	ft-lbs
Optimum Torque	18,000	ft-lbs
Maximum Torque	20,000	ft-lbs
Operating Torque	40,800	ft-lbs
Yield Torque	48,000	ft-lbs



This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.