



InterLock SPSF 7.000 in. 26.00 lb/ft P110 EB

Pipe Body

Nominal OD	7.000	inches
Nominal Weight	26.00	lb/ft
Wall Thickness	0.362	inches
Plain End Weight	25.66	lb/ft
Drift	6.151	inches
Nominal ID	6.276	inches
Grade	P110 EB	
Min Yield	125,000	lb/in ²
Min Tensile	130,000	lb/in ²
Critical Section Area	7.549	in ²
Pipe Body Yield Strength	944	kips
Min Internal Yield Pressure	11,310	psi
Collapse Pressure	7,540	psi

Connection

Connection OD	7.299	inches
Connection ID	6.220	inches
Make Up Loss	5.118	inches
Critical Section Area	6.819	in ²
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	90%	
Compression Efficiency	90%	
Connection Strength	850	kips
Uniaxial Bend Rating	69.1	° / 100 ft

Make-up Values

Minimum Torque	24,000	ft-lbs
Optimum Torque	26,000	ft-lbs
Maximum Torque	28,000	ft-lbs
Operating Torque	59,500	ft-lbs
Yield Torque	70,000	ft-lbs



This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.