





9.625 in. 53.5 lb/ft T-95 / R-95 with 10.625 in. Coupling OD

Pipe Body

Nominal OD	9.625	inches
Nominal Weight	53.50	lb/ft
Wall Thickness	0.545	inches
Plain End Weight	52.90	lb/ft
Drift	8.500	inches
Nominal ID	8.535	inches
Grade	T-95	
Min Yield	95,000	lbf/in ²
Min Tensile	105,000	lbf/in ²
Critical Section Area	15.546	in ²
Pipe Body Yield Strength	1477	kips
Min Internal Yield Pressure	9,410	psi
Collapse Pressure	7,340	psi

Connection

Coupling OD	10.625	inches
Coupling Length	12.088	inches
Make Up Loss	5.731	inches
Critical Section Area	15.546	in ²
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	100%	
Connection Strength	1477	kips
Compression Efficiency	100%	
Uniaxial Bend Rating	41.0	° / 100 ft
Min Make Up Torque	10,000	ft-lbs 
Yield Torque	76,850	ft-lbs 



Torque Data Sheet - HOSS

9.625 in. 53.5 lb/ft T-95 / R-95 with 10.625 in. Coupling OD

Min Make Up Torque	10,000 ft-lbs	Max Operating Torque	65,350 ft-lbs
Max Make Up Torque	57,650 ft-lbs	Yield Torque	76,850 ft-lbs
Optimum Torque	20,000 ft-lbs		

Representative Torque Turn Graph

