





HYDRA CBR 5.5in. x 17 lb/ft P-110 Flush Joint

Pipe Body

Nominal OD	5.500	inches
Nominal Weight	17.00	lb/ft
Wall Thickness	0.304	inches
Plain End Weight	16.89	lb/ft
Standard Drift	4.767	inches
Nominal ID	4.892	inches
Grade	P-110	
Min Yield	110,000	lbf/in ²
Min Tensile	125,000	lbf/in ²
Critical Section Area	4.962	in ²
Pipe Body Yield Strength	546	kips
Min Internal Yield Pressure	10,640	psi
Collapse Pressure	7,480	psi

Connection with Corrosion Barrier Ring

Connection OD	5.500	inches
Make Up Loss	4.463	inches
Critical Section Area	2.977	in ²
Internal Pressure Rating	8,510	psi
External Pressure Rating	7,480	psi
Tension Efficiency	60%	
Connection Strength	328	kips
Compression Efficiency	328	kips
Uniaxial Bend Rating	57	° / 100 ft
Reference Depth	12,931	Ft.
Optimal Make Up Torque	3,350	ft-lbs 
Min	3,000	ft-lbs 
Max	3,700	ft-lbs

v1.0

12/11/2019

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.

The performance properties in these data tables are calculated per API 5C3. Calculations are based on nominal wall thickness. Loads do not reflect a design safety factor for walls thinner than nominal or other defects. Reference Depth = Connection Strength / (PE Wt./Ft)*(1.5). Reference Depth includes a 1.5 design factor. However, it does not consider bending, temperature, buoyancy or other load considerations.

Torque Data Sheet - HYDRA with Corrosion Barrier Ring

HYDRA CBR 5.5in. x 17 lb/ft P-110 Flush Joint

Min Make Up Torque	3,000	ft-lbs
Max Make Up Torque	3,700	ft-lbs
Optimum Torque	3,350	ft-lbs

Nom Shoulder Torque	500	ft-lbs
---------------------	-----	--------

